Data Sheet

We make sure

FUJITSU COMPUTERS SIEMENS

Keyboard KBPC SX

Standard keyboard for business users

Issue July 2006

Pages 2

The new Fujitsu Siemens Computers standard keyboard KBPC SX leads the way to future regarding typing convenience and reliability. It offers latest technologies and an innovative design.

With combined USB and PS/2 technology, it is well prepared for every modern interface.

Ergonomically optimised keys with a rough surface and a clear defined pressure point convey a pleasant and secure typing feeling at any time.

The standard keyboard KBPC SX convinces every user due to the flat, space-saving design as well as the excellent price-performance ratio and therefore presents the optimum solution for standard PC applications.

Usability

- Connects to every PC with standard PS/2 and USB interface
- Space saving design for your workplace

Ergonomics

- Stress free and effective use through high contrast keys, ergonomic key design and a soft pressure point.

Tailor-made

- Customize your keyboard with a specific logo
- Specific keycap inscriptions for your specific designs

Reliability

- High quality and function stability through in-house development and manufacturing
- Short reaction and transportation time
- Warranty, service and spare part supply according to your needs

Modern production technology

- Abrasion-proof keys by using laser printing technology for the keycaps
- Fully automated production line
- Highest quality coupled with the best price/performance ratio guaranteed

Environmentally friendly development

- Recycling friendly by easy separation into recyclable components
- Minimized size and weight in combination with minimized use of raw materials.

Keyboard KBPC SX	
Industry standard	MF-II-compatible 104/105-keyboard layout
System compatibility	PS/2 and USB systems
Interface	Combined PS/2 and USB depending on the cable connected to the keyboard. Delivery with 2 m PS/2 cable order number USB Cable: T26139-Y3812-V1
Design	compact design, ergonomic key design, up to 6 characters possible on one keycap
Technology	Chip on board
Electrical	
Power consumption	< 50 mA at 5 V
Temperatures / Dimensions / Weight	
Ambient temperature	15°C to 32°C (as per IEC721)
Dimensions (H x W x D)	40 x 473 x 175 mm
Slope adjustment	6° and 12°
Weight	750 g

Special features	Customized laser inscription 3 additional Windows keys EURO symbol cables available in various lengths
Compliance with standards	
Product safety	IEC60950 UL 1950 CAN/CSA-C22.2 No. 60950
Ergonomics	GS mark (ZH1/618) ISO 9241-4/ EN 29241-4
Electromagnetic Compatibility	
Europe:	CE compliant with EC Directive 89/336/EEC EN 55022 class B EN 55024 EN 61000-3-2 EN 61000-3-3
North-America:	FCC part 15 class B
Operating systems	
Microsoft Windows 2000 Microsoft Windows XP	
Order Code	S26381-K397-V1**
(**: Country specific variation)	
USB cable	T26139-Y3812-V1

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.

Copyright © Fujitsu Siemens Computers, 07/2006

Published by

Fujitsu Siemens Computers
http://www.fujitsu-siemens.com/

Company stamp